Electrolux air-o-convect

Convection LW 20 GN 2/1-electric

Electrolux air-o-convect blends tradition with the latest technological research in order to satisfy the creativity and working requirements of today's professional kitchen. The air-o-convect range offers a choice of different models, providing a high degree of automation and an extensive range of accessories. The air-o-convect convection ovens with direct steam are designed to form complete cook&chill systems together with air-o-chill blast chillers/freezers, therefore, any installation can be tailored to meet the needs of the caterer. The air-o-convect ovens detailed are 20 GN 2/1 electric models.



269205

OPERATING MODES

- Convection cycle (max. 300 °C) with automatic moistener (11 settings): 0 no additional moisture (browning and gratinating); 1-2 low moisture (stewed vegetables); 3-4 medium-low moisture (au gratin vegetables, roasted meat and fish); 5-6 medium moisture (all small portions of meat and fish); 7-8 medium-high moisture (large pieces of red meat); 9-10 high moisture (large pieces of white meat, baking and pre-cooked food regeneration).
- air-o-convect ovens can cook by controlling either the cooking time or the product's core temperature through a single-sensor probe.
- Fan speeds: full and PULSE (pulse ventilation for baking and low temperature cooking). The " PULSE function" is also perfect for keeping food warm at the end of the cooking cycle and for low temperature cooking of large pieces of meat.
- Exhaust valve electronically controlled to extract excess humidity.
- air-o-clean: 4 different pre-set cycles to clean the cooking cell, according to the actual requirements. The cleaning system is built-in (no need for add-ons). Semi-automatic cleaning cycle also available.
- · Quick cooling: useful when passing to a type of cooking that requires a lower temperature than the previous one. It works automatically and manually.
- Manual injection of water in the

PERFORMANCE

- air-o-flow: blows fresh air from outside through the bi-functional fan, which pulls the air in from the backside of the oven after it is pre-heated, thus guaranteeing an even cooking process.
- Single-sensor food probe.







Electrolux air-o-convect Convection LW 20 GN 2/1-electric

CONSTRUCTION

- Stainless steel 304 throughout, with seamless joints in the cooking cell.
- Height adjustable legs.
- Double thermo-glazed door equipped with drip pans to catch condensate and prevent slippery floor for maximum security and four holding positions allowing easier loading and unloading.
- Halogen lighting in the cooking cell.
- Access to main components from the front panel.
- IPX5 water protection.
- air-o-convect ovens meet IMQ safety requirements.

	AOS202ECA2 269205
TECHNICAL DATA	
Power supply	Electric
Number of grids	20
Runners pitch - mm	63
Cooking cycles - °C	
air-convection	300
Convection	•
Meat probe	•
Automatic cleaning system	•
External dimensions - mm	
WxDxH	1243, 1107, 1795
width	1243
depth	1107
height	1795
Internal dimensions - mm	
width	933
depth	830
height	1450
Power - kW	
auxiliary	2
electric	50
cooking chamber	48
Net weight - kg.	358
Supply voltage	400 V, 3N, 50/60

Electrolux air-o-convect Convection LW 20 GN 2/1-electric

	AOS202ECA2
	269205
INCLUDED ACCESSORIES	
CONTROL PANEL FILTER-20 GN2/1 OVENS-LW	1
DOOR SHIELD 20 2/1-PRE-HEAT W/O TROLLEY	1
TROLLEY TRAY RACK 20X2/1GN,63MM PITCH-LW	1
ACCESSORIES	
1 GRID GN1/1 FOR 8 WHOLE CHICKENS(1.2KG)	922266
2 FAT FILTERS FOR 20X1/1 & 2/1 OVEN	922179
2 FRYING BASKETS FOR OVENS	922239
2 GRIDS GN 1/1 FOR CHICKENS (8 PER GRID)	922036
ADJUSTABLE WHEELS FOR 20GN LW OVENS	922280
AUTOMATIC WATER SOFTENER FOR OVENS	921305
BAKING TRAY FOR BAGUETTE GN 1/1	922288
BAKING TRAY(400X600X20)4 EDGES-ALUMINIUM	922191
BAKING TRAY(400X600X20)4 EDGES-PERF.ALUM	922190
BANQ.TROLLEY-92PLATES-85MM PITCH-20GN2/1	922055
BASKET FOR DETERGENT TANK-WALL MOUNTED	922209
DOOR SHIELD 20 2/1-PRE-HEAT W/O TROLLEY	922095
EGG FRYER FOR 8 EGGS - GN 1/1	922290
EXTERNAL REVERSE OSMOSIS FILTER FOR OVEN	922316
EXTERNAL SIDE SPRAY UNIT	922171
HEAT SHIELD FOR 20 GN 2/1 OVENS	922242
KIT INTEGRATED HACCP FOR OVENS	922275
NON-STICK U-PAN GN 1/1 H=20 MM	922090
NON-STICK U-PAN GN 1/1 H=40 MM	922091
NON-STICK U-PAN GN 1/1 H=60 MM	922092
OVEN GRILL (ALUMINIUM) GN 1/1	922289
PAIR OF 1/1GN AISI 304 S/S GRIDS	922017
PAIR OF 2/1 GN AISI 304 S/S GRIDS	922175
PASTRY TROLLEY 16(400X600)80MM-20 2/1 LW	922069
RESIN SANITIZER FOR WATER SOFTENER	921306
RETRACT. SPRAY UNIT-20 GN1/1& 2/1 OVENS	922263
THERMAL COVER FOR 20 GN 2/1-LW	922049
TRAY(400X600X38)5 ROWS-PERF.ALUM/SILICON	922189
TROLLEY TRAY RACK 16X2/1GN,80MM PITCH-LW	922046
TROLLEY TRAY RACK 20X2/1GN,63MM PITCH-LW	922044
WATER FILTER FOR 20 2/1 OVENS 1.8 L/MIN.	922104

EB/

011-06-10

53 3/4

1365 mm

400 mm

325 mm

12 25.

3 11,, 94 mm

28 25.,

731mm

69 17. 1766 mm

14 <u>19</u>" 371mm

60 mm

2 19'' 66 mm

9 7/16" 240 mm

CWI1

EI

CWI2

30 <u>3</u>" 764 mm

48 15,, 1243 mm

D

44 <u>7</u>'' 1123 mm

CWI2

ΕI

43 <u>19</u>'' 1107 mm

42" 1067 mm

2 3 ...

8 1″

205 mm

7 <u>1</u>" 179 mm

597849700

70 mm

269205

70 <u>15</u>,, 1790 mm

60 mm

59 mm

2 1/8


2 7 '' 16 '' 62 mm

54 mm

19 11,, 500 mm

CWI1

_



3 <u>15</u>'' 16' 100 mm