



Electrolux

air-o-chill Blast Chiller-Freezer 61 30 kg Tower installation

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Electrolux



air-o-chill

Blast Chiller-Freezer 61 30 kg Tower installation

726117 (AOFPS061LT)

Blast Chiller-Freezer 61 - 30 kg - for tower installation

Short Form Specification

Item No.

Unit to be Electrolux air-o-chill® Blast Chiller-Freezer 61 for tower installation. Chilling load capacity to be 30 kg from 90 °C to 3 °C in 90', freezing load capacity to be 25 kg from 90 °C to -18 °C in max 240' on up to 6 Steam table pans. Unit shall feature Micro-processor controlled Soft-chilling, hard-chilling and Blast-freezing cycles. At the end of each Blast-chilling or freezing cycle the unit shall automatically activate a holding cycle. Defrost cycle is automatically and intelligently activated: ice build up on evaporator is automatically detected and defrost activated to maximize performance efficiency. Manual activation of defrost cycle is possible. Unit does not have any heat limitation and can accept food directly from oven at cooking temperature. The unit features both time and core temperature controlled chilling cycles. One core temperature probe is provided as standard, up to three are available. Internal and external finishing in 304 Stainless steel construction. Self contained 1.5 hp air-cooled compressor. High density HCFC polyurethane insulation material.

EKIS, pc-controlled HACCP monitoring software package available at additional cost.

Main Features

- Performance guaranteed at ambient temperatures of +32°C.
- Suitable for tower installation.
- Soft Chilling (air temperature -2°C).
- Hard Chilling (air temperature -20°C).
- Probe-driven cycles feature ARTE (Algorithm for Remaining Time Estimation) to make planning the activities easier.
- Holding at +3 °C for chilling or -22 °C for freezing, automatically activated at the end of each cycle, to save energy and maintain the target temperature (manual activation is also possible)
- Control unit provides two large displays to read out: time, core temperature, cycle countdown, alarms, service information.
- Audible alarm starts when the cycle ends or terminates abnormally.
- All information related to the different operating models are recorded: date, time, cycle, core temperature, holding temperature, HACCP accordance.
- Turbo cooling: chiller works continuously at the desired temperature; ideal for continuous production.
- Control unit provides several operating settings (programmable parameters): time/core temperature according to NF and UK regulations, time/air temperature/probe personalized according to national regulations, sterilizing cycle: UV lamps built-in (on request), 3 single sensor or 3-sensor temperature probes (as accessory), ideal for meats, automatic defrosting and manual defrosting.
- Possibility to operate by time or by probe.
- Shock freezing (low air temperature adjustable up to -41°C.)
- 3-sensor core probe as standard and automatic detection of the core probe insertion.
- Hot gas defrosting system.
- Blast Freezing cycle: 25 kg from 90°C up to -18°C in less than four hours.
- Blast Chilling cycle: 30 kg from +90°C up to + 3°C in less than 90 minutes.
- Cruise: the chiller automatically sets the parameters for the quickest and best chilling (it works by probe).
- Multi-purpose internal structure is suitable for 6 grids GN 1/1 (18 positions available with 20 mm pitch) 6 grids or trays 600 x 400 mm (18 positions available with 20 mm pitch) or 9 ice-cream basins of 5 kg each (h 125 x 165 x 360).
- Two specialized cycles: P1 brings down ice-cream temperature to -14°C (measured at the core when probe is inserted). Once set temperature is reached, the temporary maintenance phase automatically begins, holding the -14°C temperature. P2 sets temperature to -36°C / -40°C for an indefinite amount of time, maintaining the ventilation active. Temperature is adjustable up to -40°C without interrupting the cycle, allowing ice-cream to be kept longer in the freezer.
- Chilling and freezing times can vary according to food quantity, density, moisture contents and type of containers. Chilling capacity according to NF regulations is 18 kg.

Construction

- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Evaporator with antirust protection.

APPROVAL: _____



Electrolux

air-o-chill **Blast Chiller-Freezer 61** **30 kg Tower installation**

- Motors and fan waterproof protected IP23.
- PC connection on request, gate RS 485.
- No water connections required.
- Stand alone printer as accessory.
- Inner cell with fully rounded corners.
- High density polyurethane insulation, 60 mm thickness, HCFC free.
- Environmentally friendly: R404a as refrigerant fluid.
- Internal and external finishing in 304 AISI stainless steel and backpanel in galvanized steel.
- Removable magnetic gasket door with hygienic design.
- Ventilator swinging hinged panel for access to the evaporator for cleaning.
- Automatic heated door frame.
- Thermostatic expansion valve to optimize the cooling unit efficiency.
- Solenoid valves.

Included Accessories

- 1 of Set of 5 stainless steel runners for 6&10 GN 1/1 blast chiller/freezers lengthwise PNC 880087
- 1 of 3-sensor probe for blast chiller and blast chiller/freezers PNC 880212

Optional Accessories

- Worktop for blast chillers and blast chillers/freezers 6x1/1GN lengthwise PNC 880027 ☐
- Set of 5 stainless steel runners for 6&10 GN 1/1 blast chiller/freezers lengthwise PNC 880087 ☐
- Kit for HACCP advanced connection for LW and CW blast chiller&freezer PNC 880183 ☐
- 3-sensor probe for blast chiller and blast chiller/freezers PNC 880212 ☐
- 1 extra single-sensor probe for blast chiller and blast chiller&freezers PNC 880213 ☐
- 2 extra single-sensor probes for blast chiller/freezers PNC 880214 ☐
- Kit of 3 single sensor probes for blast chiller/freezers PNC 880215 ☐
- Pastry rilsan grid for blast chiller, lengthwise (600x400mm) PNC 880294 ☐
- Tower execution support 6GN oven on 30kg blast chiller and freezer PNC 881049 ☐
- Plastic coated grid 1/1GN PNC 881061 ☐
- Printer for HACCP basic version (for cabinets and counters with electronic control) PNC 881532 ☐
- Pair of 1/1GN AISI 304 stainless steel grids PNC 921101 ☐
- Tray rack with wheels for 6x1/1GN ovens and bcf, 65mm pitch (std) PNC 922005 ☐
- Tray rack with wheels for 5x1/1GN ovens and bcf, 80mm pitch PNC 922008 ☐



air-o-chill
Blast Chiller-Freezer 61 30 kg Tower installation

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.


2013.03.12




Electrolux

air-o-chill Blast Chiller-Freezer 61 30 kg Tower installation

Front




Top



D = Drain
EI = Electrical connection

Side



Electric

Supply voltage:

726117(AOFPS061CT)

400 V/3N ph/50 Hz

Connected load:

1.94 kW

Circuit breaker required

Installation:

Clearance:

5 cm on sides and back.

Please see and follow detailed installation instructions provided with the unit

Capacity:

GN:

6 - 1/1 containers

Max load capacity:

30 kg

Max load capacity (gal/ lt):

30 liter

Max load capacity - trays h 65 mm

- n°:

6

Key Information:

Door hinges:

Right Side

External dimensions, Height:

1020 mm

External dimensions, Width:

896 mm

Net weight:

165 kg

Chilling-Freezing Productivity per cycle (NF Regulations):

18 kg - 18 kg

Chilling-Freezing Productivity per cycle (UK Guidelines):

30 kg - 25 kg

Thermometers:

Digital

Trays type:

600x400; GN 1/1; Ice Cream

Number of positions & pitch:

18; 20 mm

Refrigeration Data

Control type:

Electronic

Compressor power:

1,8 hp

Refrigerant type:

R404a

Refrigeration power:

1600 W

Refrigeration power at evaporation temperature:

-30 °C

Refrigerant weight:

1800 g



air-o-chill
Blast Chiller-Freezer 61 30 kg Tower installation

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2013.03.12