

Electrolux Blast Freezers

Blast Chiller/ Freezers - 56 kg 20 GN1/1

Chilling means bringing the temperature of cooked food from +90°C to +3°C in a short time lap which does not allow bacterial growth .Electrolux Blast Chillers/Freezers reduce temperature from +90°C to +3°C at food core in less than 90 minutes and down to -18°C in less than four hours: the model detailed on this sheet performs this cycle up to a 56 kg full load. After the Blast Chilling/freezing process a holding cycle starts automatically to maintain food at -18 °C. Blast chilled food has a solid 5 days shelf life without loss of flavour, nutritional values and weight. The opportunity to prepare in a single shot the food to be used in different times during the week enables a better work scheduling and therefore a sensible reduction in labour costs. The range of Electrolux Blast Chillers/freezers consists of models with built in refrigerating unit that offer an excellent all-round performance.



726630

OPERATING MODES

- Soft Chilling (Air temperature -2°C).
- Hard Chilling (Air temperature -20°C).
- All the probe-driven cycles feature ARTE (Algorithm for Remaining Time Estimation) to make planning the activities easier.
- Holding at +3°C (automatically activated at the end of each cycle).
- Turbo cooling: the chiller works continuously at the desired temperature. Ideal for continuous production.
- Automatic recognition of the insertion of the food probe (cycles piloted either by food probe temperature or by time).

- The control unit provides several operating settings: time/core temperature according to NF and UK regulations, time/air temperature/probe personalised according to national regulations, sterilizing cycle: UV lamps built-in (on request), 3 single sensor or 3-sensor temperature probes (as accessory), ideal for meats, automatic defrosting and manual defrosting. All parameters are programmable.
- Single sensor core probe as standard.
- The control unit provides two large displays to read out: time, core temperature, cycle countdown, alarms, service information.
- Two customizable cycles (P1 & P2) for each operating mode, allowing to set the time and air temperature. These programs can be converted into ice-cream specialized cycles (shape maintenance and holding).

- All information related to the different operating models are recorded: date, time, cycle, core temperature, holding temperature, HACCP accordance.
- An audible alarm starts when the cycle ends or terminates abnormally.

PERFORMANCE

- Chilling times can vary according to food quantity, density, moisture contents and type of containers. Chilling capacity according to NF regulations is 18 kg.



Electrolux

Electrolux Blast Freezers
Blast Chiller/ Freezers - 56 kg 20 GN1/1

CONSTRUCTION

- Internal and external finishing in 304 AISI stainless steel and backpanel in galvanized steel.
- High density polyurethane insulation, 60 mm thickness, HCFC free.
- Environmentally friendly: R404a as refrigerant fluid.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Inner cell with fully rounded corners.
- Door equipped with removable magnetic gasket with hygienic design.
- Motors and fan waterproof protected IP21.
- Evaporator with antirust protection.

- Ventilator (fan) swinging hinged panel for access to the evaporator for cleaning.
- Automatic heated door frame.
- Thermostatic expansion valve to optimize the cooling unit efficiency.
- Adjustable feet 150 mm high.
- Stand alone printer as accessory.
- PC connection on request, gate RS 485.

INSTALLATION

- No water connections required.
- Waste water can be plumbed into drain, but can also be collected in an optional waste container.

	RBF201 726630	RBF2016 727133
TECHNICAL DATA		
Power supply	Electric	Electric
Productivity per cycle - kg.		
NF Regulations - chilling / freezing	43.2	
UK Guide lines - chilling / freezing	64, 56	
Gross capacity (D.I.N. 8952) - l.	560	560
Cooling unit	Built-In	Built-In
External dimensions - mm		
width	800	800
depth/with open doors	835, 1570	835, 1570
height	2230	2230
Door hinges	Right Side	Right Side
Trays type	GN 1/1; 600x400	GN 1/1; 600x400
Max load capacity - trays h 65 mm - n°	12	
Compressor power - HP	3	2.8
N° defrost in 24 hrs.	3	
Refrigerant type	R404a	R404a
Refrigerant quantity - g.	3600	3600
Refrigeration power - W	9054	4520
Refrigerant power		
at evaporation temperature - °C	-5	-5
Power - kW		
installed-electric	3.93	4.216
Net weight - kg.	235	235
Power supply - V, phases, Hz	400 V, 3N, 50	220 V, 3N, 60
INCLUDED ACCESSORIES		
1 SINGLE-SENSOR PROBE-BL.C/FREEZERS LW	1	1
REMOVABLE TRAY SUPPORT RACK FOR 20 GN1/1	4	4
ACCESSORIES		
1 SINGLE-SENSOR PROBE-BL.C/FREEZERS LW	880213	880213
3 SINGLE-SENSOR PROBES-BL.C/FREEZERS LW		880215
3-POINT-SENSOR PROBE-BL.C/FREEZERS LW	880212	880212
60-MM PITCH ROLL-IN RACK FOR 20X1/1	922203	922203
80MM PITCH ROLL-IN RACK 14X1/1GN	922205	922205
KIT HACCP ADVANCED CONNECT. BC/BCF LW+CW	880183	880183
PAIR OF 1/1 GN AISI 304 S/S GRIDS	921101	921101
PLASTIC COATED GRID-600X400 MM	880864	880864
PRINTER HACCP BASIC VERS-REF.ELECR.CONTR	881532	881532
RACK RAILS FOR VERTICAL BLAST CHILLER	881182	881182
REMOVABLE TRAY SUPPORT RACK FOR 20 GN1/1	881010	881010
RILSAN COATED GRID	881061	881061
TROLLEY FOR 20X1/1 ROLL-IN RACK	922132	922132


HDBA030

2011-06-10

Subject to change without notice

Electrolux Blast Freezers
Blast Chiller/ Freezers - 56 kg 20 GN1/1

726630, 727133



110719-110723
726624-726630
728592-728594

HDBA030

2011-06-10

Subject to change without notice

LEGEND	RBF201 726630	RBF2016 727133
	400 V, 3N, 50	220 V, 3N, 60

EI - Electrical connection