



Electrolux

Digital Undercounter Freezer Counter 1 Door and 2 Drawers (without worktop)

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Electrolux



Digital Undercounter

Freezer Counter 1 Door and 2 Drawers (without worktop)

728570 (HBF1P2CN)

1-door and 2-drawer freezer counter, -20-15°C, AISI 304, without worktop

Short Form Specification

Item No.

Internal and external doors, front and side panels in 304 AISI stainless steel. No worktop. N.1 door and n.2x1/2 drawers. Built-in refrigeration unit. Ventilated. Refrigerant R404a. High-density expanded polyurethane foam, 50 mm in thickness, with cyclopentane injection. Digital control panel. Evaporator in aluminium. Completely automatic defrosting and automatic evaporation of defrost water obtained by hot gas. Suitable to operate in ambient temperatures up to +43°C. Temperature range: -15/-20°C. CFC and HCFC free. Feet in 304 AISI stainless steel, adjustable in height. Pre-arranged for drain pipe.

Supplied with n.1x1/1GN Rilsan grid and n. 3 pairs of runners.

Main Features

- Digital control panel with temperature display.
- Forced air circulation for rapid cooling and an even temperature distribution.
- CFC and HCFC free (ecological refrigerant type: R404a, - gas in foam: cyclopentane).
- Suitable for use in ambient temperatures of up to 43 ° C.
- Compliant to CE requirements for safety.
- Anti-tilt runners accept GN1/1 trays and grids.
- Adjustable temperature range from -15°C to -20°C to suit all storage requirements.

Construction

- Rounded internal corners for ease of cleaning.
- Mounted on Stainless steel adjustable legs to give 150 mm clearance for ease of cleaning.
- Access to all components from the front.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- 304 AISI stainless steel internal and external doors, front and side panels. Evaporator in aluminium.
- Pre-arranged for drain-pipe.
- Built-in compressor.
- 50 mm insulation thickness for energy saving.
- Constructed in Stainless steel with Scotch Brite finish to meet the highest hygiene standards.

Included Accessories

- 1 of 1/1GN grey rilsan grid PNC 881435

Optional Accessories

- Wheels kit PNC 880025
- Reversibility door kit PNC 880046
- Lock kit for refrigerated counters PNC 880130
- Kit 2 stainless steel grids GN1/1 for refrigerated counters PNC 880139
- Stainless steel internal structure to support PNC 880140 6 grids (right and left)
- Kit for integrated HACCP advanced connection (Carel) for digital ecostore cabinets and counters (not for ecostore Touch models) PNC 880252
- Printer for HACCP basic version (for cabinets and counters with digital control) PNC 881457

APPROVAL: _____



Electrolux

Digital Undercounter Freezer Counter 1 Door and 2 Drawers (without worktop)

Electric

Supply voltage:

728570(HBF1P2CN)

230 V/1N ph/50 Hz

Connected load:

0.52 kW

Key Information:

Door hinges: Right Side

External dimensions, Height: 800 mm

External dimensions, Width: 1238 mm

Number and type of doors: 1 Full

Internal Dimensions (depth): 580 mm

Internal Dimensions (height): 543 mm

Gross capacity: 265 lt

Net weight: 120 kg

Noise level: 60 dBA

Depth with doors open: 1098 mm

Number and type of grids
(included): 1 - GN 1/1

N° of drawers: 2x1/2

Refrigeration Data

Control type: Digital

Compressor power: 3/4 hp

Refrigerant type: R404a

Refrigeration power: 802 W

Refrigerant weight: 160 g

Operating temperature min.: -20 °C

Operating temperature max.: -15 °C

Operating mode: Ventilated



Digital Undercounter
Freezer Counter 1 Door and 2 Drawers (without worktop)

The company reserves the right to make modifications to the products
without prior notice. All information correct at time of printing.

2012.09.04