

# Electrolux concept counters

## Freezers without top

Electrolux Professional has designed and produced a complete range of refrigerated tables, that combines the dual function of worktop and refrigerated table. This versatility allows notable savings in space while offering functional and modular solutions to kitchen requirements. The models represented here have a temperature range of -15 to -20 °C and are available with built-in refrigerating unit, in various combinations of doors and drawers and without worktop.



- Built-in compressor.
- Suitable for use in ambient temperatures of up to 43°C.
- Constructed in stainless steel to meet the highest hygiene standards.
- Rounded internal corners for ease of cleaning.
- Mounted on stainless steel legs with plastic interior to give 150 mm clearance for ease of cleaning the floor.
- Adjustable temperature range from -15°C to -20°C to suit all storage requirements.
- Anti-tilt runners accept GN1/1 trays and grids.
- Digital control with temperature display.
- Forced air circulation for rapid cooling and an even temperature distribution.
- Internal and external doors, front and side panels in 304 AISI stainless steel.
- Evaporator in aluminium.
- Access to all components from the front panel.
- Pre-arranged for drain-pipe.
- In compliance with CE requirements.
- CFC and HCFC free (ecological refrigerant type: R404a, - gas in foam: cyclopentane).
- 50 mm insulation thickness for energy saving.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.



**Electrolux**

**Electrolux concept counters  
Freezers without top**

	<b>HBF1P2CN 728570</b>	<b>HBF2PN 728569</b>	<b>HBF3PN 728571</b>	<b>HBF2P2CN 728573</b>
<b>TECHNICAL DATA</b>				
Operating temperature - min/max °C	-20/-15	-20/-15	-20/-15	-20/-15
Operating mode	Ventilated	Ventilated	Ventilated	Ventilated
Type of stainless steel				
external	304 AISI	304 AISI	304 AISI	304 AISI
internal	304 AISI	304 AISI	304 AISI	304 AISI
Gross capacity (D.I.N. 8952) - l.	265	265	415	415
External dimensions - mm				
width	1238	1238	1721	1721
depth/with open doors	700, 1098	700, 1098	700, 1098	700, 1098
height	800	800	800	800
Internal dimensions - mm				
depth	580	580	580	580
height	543	543	543	543
N° of drawers	2x1/2			2x1/2
Door hinges	Right Side	1 Left+1 Right	1 Left+2 Right	1 Left+1 Right
N° and type of grids (included)	1, GN 1/1	2, GN 1/1	3, GN 1/1	2, GN 1/1
Compressor power - HP	3/4	3/4	3/4	3/4
N° defrost in 24 hrs.	4/28'	4/28'	4/28'	4/28'
Refrigerant type	R404a	R404a	R404a	R404a
Refrigerant quantity - g.	160	160	200	200
Refrigeration power - W	802	910	910	910
Power - kW				
installed-electric	0.52	0.52	0.7	0.7
Noise level - dBA	60	60	59.5	59.5
Net weight - kg.	120	115	137	147
Power supply - V, phases, Hz	230 V, 1N, 50	230 V, 1N, 50	230 V, 1N, 50	230 V, 1N, 50
<b>INCLUDED ACCESSORIES</b>				
1/1 GN GREY "RILSAN" GRID	1	2	3	2
<b>ACCESSORIES</b>				
KIT 2 S/S GRIDS GN1/1 FOR REFRIG.TABLES	880139	880139	880139	880139
KIT 4 WHEELS (2 W/BRAKE)+4 (40MM)SPACERS	880025	880025	880025	880025
KIT DOOR REVERSIBILITY FOR REF.TABLES	880046	880046	880046	880046
KIT HACCP EKIS	922166	922166	922166	922166
KIT INTEGRATED HACCP-DIG. REFR. (IR33)	880252	880252	880252	880252
LOCK KIT FOR REFRIGERATED TABLES	880130	880130	880130	880130
PRINTER HACCP BASIC VERS-REF.DIGIT.CONTR	881457	881457	881457	881457
S/S STRUCTURE TO SUPPORT 6 GRIDS (R+L)	880140	880140	880140	880140

HBBD020

2011-06-10

Subject to change without notice