

440 lt refrigerated counters

The Electrolux range of refrigerated counters combines the convenience of worktop space with cold storage located below. This range of counters is constructed in 304 AISI stainless steel to meet the highest hygiene standards. The range is comprised of three sizes of counters, with built-in or remote compressor units, in various door or drawer configurations and in refrigerator or freezer versions. The models detailed on this sheet are refrigerated counters with 3 sections and operate at a temperature range of -2°C to $+10^{\circ}\text{C}$.



726560

EASY TO INSTALL

- Mounted on legs with height adjustment.
- Built-in compressor to suit operating conditions.
- Suitable for use in ambient temperatures of up to 43°C .

EASY TO CLEAN

- Constructed in 304 AISI stainless steel to meet the highest hygiene standards.
- Rounded internal corners for ease of cleaning.
- Mounted on stainless steel legs to provide 150 mm clearance for easy floor cleaning.

EASY TO USE

- Adjustable temperature range from -2°C to $+10^{\circ}\text{C}$ to suit meat, fish and dairy storage requirements.
- Anti-tilt runners accept GN1/1 containers.
- Combination of doors and drawers to suit varying needs, with the possibility to change the configuration on site.
- Electronic microprocessor control with external digital temperature display.
- Forced air circulation for rapid cooling and an even temperature distribution.
- Worktop in 304 AISI stainless steel 50 mm in thickness.

EASY TO MAINTAIN

- Access to all components from the front.

EASY ON THE ENVIRONMENT

- CFC and HCFC free (ecological refrigerant type: R134a, - gas in foam: cyclopentane).
- 60 mm insulation thickness for energy saving.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- All models comply with the standards required by the main international approval bodies and are CE marked.

**Electrolux HD-Line
440 lt refrigerated counters**

	RCDR3M30 726559	RCDR3M22 726560	RCDR3M14 726561	RCDR3M06 726562	RCDR3M30T 727077	RCDR3M23T 727078	RCDR3M16T 727080
TECHNICAL DATA							
Operating temperature - min/max °C	-2/10	-2/10	-2/10	-2/10	-2/10	-2/10	-2/10
Operating mode	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Gross capacity (D.I.N. 8952) - l.	440	440	440	440	440	440	440
Cooling unit	Built-In	Built-In	Built-In	Built-In	Built-In	Built-In	Built-In
External dimensions - mm							
width	1759	1759	1759	1759	1759	1759	1759
depth/with open doors	700, 1110	700, 1110	700, 1110	700, 1110	700, 1110	700, 1110	700, 1110
height	850	850	850	850	800	800	800
Worktop type	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	none	none	none
Top material	304 AISI	304 AISI	304 AISI	304 AISI			
Min/Max internal humidity - %	80/95	80/95	80/95	80/95	80/95	80/95	80/95
N° of drawers		2	4	6x1/2		3x1/3	6x1/3
Door hinges	1 Left+2 Right	1 Left+1 Right	Left		1 Left+2 Right	1 Left+1 Right	Left
N° and type of grids (included)	3, GN 1/1	2, GN 1/1	1, GN 1/1	GN 1/1	3, GN 1/1	2, GN 1/1	1, GN 1/1
Compressor power - HP	1/4	1/4	1/4	1/4	1/4	1/4	1/4
N° defrost in 24 hrs.	3/15'	3/15'	3/15'	3/15'	3/15'	3/15'	3/15'
Refrigerant type	R134a	R134a	R134a	R134a	R134a	R134a	R134a
Refrigerant quantity - g.	220	220	220	220	220	220	220
Refrigeration power - W	358	358	358	358	358	358	358
Refrigerant power							
at evaporation temperature - °C	-10	-10	-10	-10	-10	-10	-10
Power - kW							
installed-electric	0.34	0.34	0.34	0.34	0.34	0.34	0.34
Net weight - kg.	142	150	158	166	142	142	142
INCLUDED ACCESSORIES							
1/1 GN GREY "RILSAN" GRID	3	2	1		3	2	1
ACCESSORIES							
1/1 GN GREY "RILSAN" GRID	881435	881435	881435	881435	881435	881435	881435
2 WHEELS FOR REFRIGERATORS/REFRIG.TABLES	880539	880539	880539	880539	880539	880539	880539
KIT 1 BOTTLER+1 DRAWER FOR REFR.COUNTER	881516	881516	881516	881516	881516	881516	881516
KIT 1 DOOR FOR REFRIGER.COUNTER	881517	881517	881517	881517	881517	881517	881517
KIT 2 DRAWERS 1/2+RACK-HD REF.COUNTERS	881514	881514	881514	881514	881514	881514	881514
KIT 3 DRAWERS 1/3+RACK-HD REF.COUNTERS	881515	881515	881515	881515	881515	881515	881515
KIT INTEGRATED HACCP-DIG. REFR. (IR33)	880252	880252	880252	880252	880252	880252	880252
LOCK FOR REFRIGERATED COUNTERS	881499	881499	881499	881499	881499	881499	881499
PLASTIC CONTAINER GN 1/1 H=100 MM	811451	811451	811451	811451	811451	811451	811451
PLASTIC CONTAINER GN 1/1 H=150 MM	881040	881040	881040	881040	881040	881040	881040
PLASTIC CONTAINER GN 1/1 H=65 MM	881038	881038	881038	881038	881038	881038	881038
PRINTER HACCP BASIC VERS-REF.DIGIT.CONTR	881457	881457	881457	881457	881457	881457	881457
WORKTOP FOR REFR.COUNTER-3 COMPARTMENTS					880257	880257	880257
WORKTOP+UPSTAND FOR REF.COUNTER-3 COMP.					880260	880260	880260


HBAB040

2011-06-10

Subject to change without notice

**Electrolux HD-Line
440 lt refrigerated counters**

726559, 726562, 726561, 726560



HBAB040

2011-06-10

	RCDR3M30 726559	RCDR3M22 726560	RCDR3M14 726561	RCDR3M06 726562
LEGEND				
D - Water drain	16mm	16mm	16mm	16mm
ED - Remote electrical connection				●
EI - Electrical connection	230 V, 1N, 50	230 V, 1N, 50	230 V, 1N, 50	230 V, 1N, 50

Subject to change without notice