

Digital Cabinets 400lt Line 1 Door Fish Refrigerator - Stainless steel

ITEM #
MODEL #
NAME #
SIS #
AIA #



Digital Cabinets

400lt Line 1 Door Fish Refrigerator - Stainless steel

730183 (R04NVF4F)

1-door fish refrigerator 400lt, -6+6°C, stainless steel, ventilated

Short Form Specification

Item No.

Exterior in stainless steel. Interior in white High Impact Polystyrene with rounded corners and 45mm thick insulation. Right hinged full door with lock, reversible on-site. Built-in refrigeration unit; ventilated operating mode; automatic defrost by heating elements and evaporation of defrost water only through drain; digital control and temperature display. For ambient temperatures up to 38 °C. HCFC, CFC and HFC free insulation and R134a refrigerant gas

Supplied with n. 4 containers (with stainless steel false bottom) mm600x400 and n. 1 container (with stainless steel false bottom) 600x300mm.

Main Features

- Digital control panel allowing the easy and precise setting and control of the internal temperature.
- Shelf runners are thermoformed and are incorporated in the internal structure to be easily cleanable.
- Model requires only 1 phase 220/240V supply and can be plugged straight into an existing power socket.
- Very quiet operation.
- Whole interior cell with rounded corners is white thermoformed polystyrene, which is impact resistant.
- No joints whatsoever to eliminate dirt traps.
- Simple refrigeration system easily accessible from the rear of the units.
- Fan assisted cooling for even temperature distribution.
- Suitable for use in ambient temperatures of up to 38 ° C.

Construction

- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- All models in range are finished in top quality materials to aid durability.
- CFC and HCFC free (ecological refrigerant type: R134a, gas in foam: cyclopenthane).

Included Accessories

• 5 of Pvc container with false bottom for PNC 881072 400lt

Optional Accessories

- Pair of grids for 400lt refrigerator, white PNC 880292 □
- 2 wheels for HD refrigerated counter and 400, 600 & 1300lt benefit refrigerated cabinets
- Pvc container with false bottom for 400lt
 PNC 881072 □
- Printer for HACCP basic version (for cabinets and counters with digital control)


 PNC 881457 □

APPROVAL:



Digital Cabinets 400lt Line 1 Door Fish **Refrigerator - Stainless steel**

Front



Electric

Supply voltage:

730183(R04NVF4F) 230 V/1N ph/50 Hz

Connected load: 0.35 kW

Key Information:

Door hinges: Right Side External dimensions, Height: 1755 mm **External dimensions, Width:** 703 mm External dimensions, Depth with Doors Open: 1310 mm

Gross capacity: 400 It Noise level: 56 dBA Type of external material: Stainless Steel **External door material:** Stainless Steel

Refrigeration Data


Control type: Digital Compressor power: 1/3 hp Refrigerant type: R134a Refrigeration power: 398 W

Refrigeration power at

-12 °C evaporation temperature: Refrigerant weight: 200 g Min/Max internal humidity: 70%/85% Operating temperature min.: -6 °C 6°C Operating temperature max.: **Built-in Compressor and Refrigeration Unit** Operating mode: Ventilated **Cooling unit:** Built-In

Defrost type: Automatic (electrical)

Top



EI = Electrical connection

Side

